



TEL 32 SELF-CONTAINED EMERGENCY LUMINAIRES (LED)



Dimension : 300L x 130W x 64H

SPECIFICATION

Model	: TEL 32
System Mode	: Non Maintained
Emergency Duration	: 2 hours
Lamp	: 2 x 1W High Output white L.E.D.
Battery	: 3.6V 2.5AH High temperature nickel cadmium battery
Recharge Period	: 16 fi 24 hours
Battery Protection Monitoring	: Low Voltage cut off to prevent from over charging : Green L.E.D. †ON† indicates charging Equipped with push test switch to simulate power failure
Input Voltage	: 240V 50Hz +/-10%
Charger	: Constant current, Dual rate
Housing	: Injection moulded fire retardant ABS housing
Dimension	: 300L x 130W x 64H
Weight	: 0,9kg
Mounting	: Surface mounted direct to wall
Warranty	: 1 Year
Compliance	: SS 563 : 2010, SS 263 PART 2 : 1998



Note : Due to continuous development and improvement, our company reserves the right to change specifications without notice.

LUMINAIRE DATA SHEET

CUT-SHEET	QTY	LEGEND

LUMINAIRE DESCRIPTION: PNE TEL32 LED TWINLAMP NON-MAINTAINED EMERGENCY LUMINAIRE C/W NI-CDA BATTERIES & 2X1W LED

IMAGES/DIMENSIONS



300LX130WX64H

TECHNICAL SPECIFICATION

Brand / Model : PNE/TEL32
 Lamp Source : 2X1W LED LAMP
 Lamp Output : 40 LUMENS PER LAMP
 Avg Lamp Life : 15,000 BURNING HOURS
 Material : INJECTION MOULDED FIRE RETARDANT ABS
 Diffuser : ACRYLIC DIFFUSER
 IP Rating : IP30

PNE TRANSLITE PTE LTD