



TEX 300S SELF-CONTAINED EMERGENCY LED EXIT SIGN



SPECIFICATION

Model	: TEX 300S
System Mode	: Maintained
Emergency Duration	: 3 hours
Lamp	: High Output L.E.D. array
Battery	: 2.4V High temperature nickel cadmium battery
Recharge Period	: 16 – 24 hours
Battery Protection	: Low Voltage cut off to prevent battery from over discharging
Monitoring	: Green L.E.D. "ON" indicates charging Equipped with micro switch to simulate power failure
Input Voltage	: 240V 50Hz
Charger	: Constant current, Dual rate
Housing	: Injection moulded fire retardant ABS housing
Dimension	: 347L x 38W x 244H
Weight	: 2.0Kg
Mounting	: Surface mounted to wall / Suspended from ceiling
Warranty	: 1 year
Compliance	: SS 563 ; 2010, SS IEC 60598-2-22
Power Consumption	: 3.90 Watt
IP Rating	: IP 40

Note : Due to continuous development and improvement, our company reserves the right to change specifications without notice.

PNE translite PTE LTD

CO REG NO.: 199100450H ADDRESS: 996 BENDEMEER ROAD, #07-07 SINGAPORE 339944
TEL: (65) 6291 0698 FAX: (65) 6295 8440 EMAIL: translite@pne.com.sg WEBSITE: www.pne.com.sg

